

### 1100 ANTICHIP UNDERBODY COATING



# Product Description:

- Synthetic resin and rubber based coating.
- Durable protection against stone chip and corrosion.
- Fast drying.
- **○** Long lasting elasticity.
- Excellent adhesion properties.

### EN 1100 ANTICHIP UNDERBODY COATING

## Product Application:



Shake well before use 2-3min.



Compliant - HVLP Spray gun 2K Acrylic Paints Synthetic Paints



Underseal Spray gun Nozzle: 4 – 5mm Pressure: 5-6 bar



Drying time 2h / 23°C 30min /60°C



or Application with brush



Use protective equipment



Flash off 5-10 min / 23°C



Product application should be done in accordance to this Technical Data Sheet



Compliant Spray gun Nozzle: 1.3 – 1.5 mm 1 x EN 4100 Plast-O-Clear = 10-15 micron (recommended)



Flash off 5-10 min / 23°C

#### EN 1100 ANTICHIP UNDERBODY COATING

#### Flash Point:

9°C/48°F

#### **Specific Gravity:**

 $1.2g/cm^{3}$ 

#### Solid Content (No thinner):

50% Weight

#### VOC (2004/42/EC)

2004/42/IIB(e)(840)460

The EU limit value for this product category in ready for use form is max 840 g/l of VOC. The VOC value of this product in ready for use form is max. 460 g/l.

#### **Theoretical Coverage:**

3 -  $5\text{m}^2$  / l at 150 -  $200\mu\text{m}$ 

#### Cleaning of equipment:

Clean after use with EN 7100 SOLVENT NORMAL

#### **Remarks:**

- Allow additional time for preheating up to panel temperature
- It can be used by countries that do not adopt the VOC legislation as well.
- Store in a cool place.Shelf life of 24 months in sealed containers.

For professional use only. The information provided on this sheet has been carefully selected through a series of laboratory researches. It is based upon our best knowledge at the time of issue. This data is only for information purposes. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for updates or further information if needed for his purpose. The intellectual property of the product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Version 1, Dec 2011.